



CALLE PABO DE OLAVIDE 407 TERCER PISO, URB. LA COLONIAL CALLAO - CALLAO

IR Touch Interactive Flat Panel Display

Model	LTQ65RK3576	LTQ75RK3576	LTQ86RK3576	LTQ98RK3576
Size	65"	75"	86"	98"
Image				
Display parameters				
Panel size	65"	75"	86"	97.5"
Resolution	3840*2160(pixels)	3840*2160 (pixels)	3840*2160(pixels)	3840*2160(pixels)
Pixel pitch	0.372 mm x 0.372 mm	0.4296mm x 0.4296 mm	0.4935 mm x 0.4935 mm	0.1625 (H)x 0.4875 (V)
Brightness	350cd/m ² (typ.)	350cd/m ² (typ.)	350cd/m ² (typ.)	350cd/m ² (typ.)
Contrast	5000:1 (typ.)	4000:1 (typ.)	4000:1 (typ.)	6000:1 (typ.)
Color	16.7M(8bit)	16.7M(8bit)	16.7M(8bit)	16.7M(8bit)
Response time	8ms (typ.)	8ms (typ.)	8ms (typ.)	8ms (typ.)
Viewing area	1428.48mm(H) x 803.52mm(V)	1649.66mm(H) x 927.936mm(V)	1895.04mm(H) x 1065.96mm(V)	2158.85mm(H) x 1214.35mm(V)
View Angle	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)
Service life	50,000 hrs (typ.)	50,000 hrs (typ.)	50,000 hrs (typ.)	50,000 hrs (typ.)
Android function parameters				
Android version	Android 14.0			
CHIPSET	RK3576			
CPU	ARM 4x Cortex-A72 @ 2.2GHz + 4x Cortex-A53			
GPU	ARM Mali-G52 MC3/MP3			
Storage	8GRAM128GMemory			
Resolution	3840*2160			
Network	10/100/1000MEthernet/WiFi-2.4G/5G			
Video Format	MPEG2-4.H.264,H.265,TS,Realmedia,wait			
Image Format	JPG, JPEG, BMP, PNG,wait			
Child lock	support			
Wireless screen projection	support			
Annotation	Support full channel annotation			
Backside Connection ports				
SPDIF OUT	*1			
RS232	*1			
RJ45 IN	*1			
LINE IN	*1			
LINE OUT	*1			
TYPE-C	*1			
Touch USB-B	*1			
HDMI OUT	*1			
HDMI IN	*1			
USB2.0(Android)	*2			
USB3.0 (Android)	*1			
WIFI	2.4G/5G (Wifi 6 for option)			
BT	5.2 (5.4 for option)			
Touch parameters				
Touch Type	Infrared sensor			
Touch points	Android 20 /Windows 40			
Touch height	2.5mm			
Running the system	Windows7/8/10/11,Mac OS,Andriod			
Ambient light sensor				
Light sensor	Support			
Front Side ports				
Power Button	One button (front, three-in-one power switch with indicator light)			
TYPE-C	*1 (USB data only, full function USB-C is for optional)			
HDMI IN	*1			
Touch USB-B	*1			
USB2.0 (Public)	*2			
Camera				
MIC	Omnidirectional Linear Isometric Microphone			
Signal-to-Noise Ratio	≥39dB			
Pickup distance	8 meters			
Support functions	Echo cancellation, beamforming, ambient noise suppression			
Built-in camera	13MP/48MP for Option			
Power supply				
Speaker power	15W*2	15W*2	15W*2	15W*2
Standby power	≤0.5W	≤0.5W	≤0.5W	≤0.5W

Power supply for the whole machine	AC100V-240V,50-60 Hz	AC100V-240V,50-60 Hz	AC100V-240V,50-60 Hz	AC100V-240V,50-60 Hz
Total power (Excluding OPS)	≤180W	≤260W	≤340W	≤580W
Work Environment				
Operating temperature		0°C~40°C		
Operating humidity		20%~85%(No condensation)		
Storage temperature		-10°C~60°C		
Storage humidity		10%~60%(No condensation)		
Material				
Housing Material		Aluminum frame + tempered glass + metal cover		
Shell color		Black (white frame / gray are optional)		
Tempered glass hardness		≥7		
Tempered thickness		3.2mm		
Dimensions (W*D*H)				
Machine dimensions (W*D*H)	1485 (L) *100.8 (W) 900.1 (H) (H) mm	1707.2 (L) *100.8 (W) *1025.3 (H) mm	1953.4 (L) *100.8 (W) *1163.9 (H) mm	2218.2 (L) *93.8 (W) *1317.7 (H) mm
Packing dimensions (W*D*H)	1580 (L) *205 (W) *1000 (H) mm	1810 (L) *205 (W) *1150 (H) mm	2060 (L) *205 (W) *1331 (H) mm	2350*230*1450mm
VESA size	400*500mm, 4*M8 screws	400*600mm, 4*M8 screws	400*800mm, 4*M8 screws	600*900mm, 4*M8 screws
Weight				
net weight	36KG ±1.5 Kg	50KG ±1.5 Kg	63KG ±1.5 Kg	85KG ±1.5 Kg
Gross Weight	44KG ±1.5 Kg	60KG ±1.5 Kg	76KG ±1.5 Kg	100KG ±1.5 Kg
Accessories				
Remote Control			*1	
Power cord			*1	
Warranty card			*1	
Certificate			*1	
Touch pen			*2	
Wall Mount			*1	
HDMI Cable			*1	
Touch Cable			*1	